

Ride-on floor scrubber driers

A24 7100



Standard equipment



- 2 x 5.511.1097
PPL brush Ø 483 mm - 19"



- 4.508.0217
Front squeegee blade L.1270 mm
Shore 40 Th. 4 mm
- 4.508.0216
Rear squeegee blade L.1345 mm
Shore 33 Th. 6 mm



Watch the video on youtube:
www.youtube.com/fasavideo

A24 7100

Code	8.578.0009
Power supply	36V DC
Equipped with	-
Scrubbing width	1020 mm
Squeegee width	1250 mm
Max working capacity	7140 m ² /h
Detergent tank capacity	200 l.
Recovery tank capacity	210-240 l.
Traction type	900W/front motorwheel
Brush/Vacuum motor power	1500W/600 W

A24 7100

- Suitable for maintenance and deep cleaning of medium and large areas (up to 6.000 m²)
- More than 90/120 kg of constant pressure on the brushes
- Large load tank capacity, resulting in reduced number of stops and maximum use of battery charge for effective operation of the machine
- Stability even when fully loaded
- Front independent wheel-drive with tight steering radius
- Easy access to electrical components
- Automatic brush plate lifting system
- Automatic squeegee lifting system
- Automatic squeegee lifting while reverse going
- Automatic control system for brush rotation and detergent water outflow
- Antifoam device
- Self-levelling brush plate
- Hour meter
- High-performance batteries resulting in high-working efficiency.

Ride-on floor scrubber driers



The unique anti foam device dramatically reduces the foam generation and prevents it from touching the suction motor, thus protecting its operation.

The electronic floating switch stops suction when the tank is full.

Large tank opening for fast and easy cleaning and sanitation.

The strong V-shaped floor squeegee made of steel profile is widely adjustable and allows to combine the operation of the rubber blades with the high suction power, to get a perfect drying result on every surface. The special filter box retains solid debris and prevents the obstruction of the suction hose.



A 24 scrubbers are easy to use thanks to the simple and user friendly controls. From the control panel the operator can adjust the maximum forward speed and the quantity of cleaning solution outflow, selecting the options most suitable to the dirt type. Job is simplified and made faster by the automatic lifting of the squeegee and of the brush plate.

Thanks to the optimal weight distribution and to the use of strong oil-proof polyurethane wheels the drive is perfect in all working conditions. The emptying of the solution water tank is quick with a simple and easy accessible mechanical tap.



Optional accessories:



- 0.107.0009
Battery box Pb-acid
36V 360Ah C5
- 0.107.0012
Gel battery box
36V 320Ah C5



- 0.108.0003
Battery Charger 24/36V
50/60A - 220-240/50-60



- 4.508.1167 Polyurethane
front blade L.1270 TH. 4
- 4.508.0897 Polyurethane
rear blade L.1345 TH. 6



- 2 x 5.511.1098
Tynex brush Ø 483 mm-19"
- 2 x 5.511.1128
PPL 0,03 brush Ø 483 mm-19"
- 2 x 5.511.1206
PES brush Ø 483 mm - 19"



- 2 x 5.511.1099
EWU pad driver Ø 483 mm-19"



- 6.508.0034 - Ø 483 mm -
19" - beige (5 pcs.)
- 6.508.0041 - Ø 483 mm -
19" - green (5 pcs.)
- 6.508.0048 - Ø 483 mm -
19" - black (5 pcs.)