

Ride-on floor scrubber driers

A35 8500



Standard equipment



- 3 x 5.511.1109
PPL brush Ø 406 mm - 16"



- 4.508.0219
Front squeegee blade L.1500 mm
Shore 40 Th. 4 mm
- 4.508.0218
Rear squeegee blade L.1580 mm
Shore 33 Th. 6 mm



Watch the video on youtube:
www.youtube.com/fasavideo

A35 8500

Code	8.572.0004
Power supply	36V DC
Equipped with	-
Scrubbing width	1220 mm
Squeegee width	1450 mm
Max working capacity	8540 m ² /h
Detergent tank capacity	280 l.
Recovery tank capacity	315-340 l.
Traction type	3 x 600W/3 wheels drive
Brush/Vacuum motor power	3 x 1000W/600 W

A35 8500

- Suitable for maintenance and deep cleaning of medium and large areas (up to 7.000 m²)
- More than 120-170 kg of constant pressure on the brushes
- 300 litres solution tank capacity allows exceptional autonomy and productivity
- Stability even when fully loaded
- Innovative traction system with three independent motor wheels controlled by electronic cards
- Easy access to electrical components
- Automatic brush plate lifting system
- Automatic squeegee lifting system
- Automatic squeegee lifting while reverse going
- Automatic control system for brush rotation and detergent water outflow
- Antifoam device
- Self-levelling brushes, hour meter, solenoid valve. High-performance batteries resulting in high-working efficiency

Ride-on floor scrubber driers



Designed to perform the hardest work and to resist even to extreme stresses with maximum comfort; the frame is made of steel profiles with a thickness varying from 5 to 12 mm, protected with a high resistance corrosion-proof paint. The unique anti foam device dramatically reduces

the foam generation and prevents it from touching the suction motor, thus protecting its operation. The electronic floating switch stops suction when the tank is full. Large tank opening for fast and easy cleaning and sanification. The cleaning solution tank with an exceptional capacity



of 300 liters and the high autonomy of the battery ensure a productivity at the top of the range. The wide rear opening allows for an easy and quick refilling of the cleaning solution tank. The motorwheels, designed and built by Fasa, grant optimal performances and exceptional reliability

(over 30.000 hours). The innovative 3wheel drive system ensures perfect traction in every operating condition. The high power of the three motorwheels allows the machine to get over remarkable slopes.



Optional accessories:



- 0.107.0010
Battery box Pb-acid
36V 525Ah C5
- 0.107.0013
Gel battery box
36V 400Ah C5



- 0.108.0003
Battery Charger 24/36V
50/60A - 220-240/50-60



- 4.508.1167 Polyurethane
front blade L.1270 TH. 4
- 4.508.0897 Polyurethane
rear blade L.1345 TH. 6



- 3 x 5.511.1110
Tynex brush Ø 406 mm-16"
- 3 x 5.511.1120
PPL 0,03 brush Ø 406 mm-16"
- 3 x 5.511.1204
PES brush Ø 406 mm - 16"



- 3 x 5.511.1111
EWU pad driver Ø 406 mm-16"



- 6.508.0031 - Ø 406 mm - 16" - beige (5 pcs.)
- 6.508.0038 - Ø 406 mm - 16" - green (5 pcs.)
- 6.508.0045 - Ø 406 mm - 16" - black (5 pcs.)